

**4-02 GRAVEL BASE****4-02.1 Description**

This Work shall consist of constructing one or more layers of gravel base upon a prepared Subgrade in accordance with these Specifications and in conformity with the lines, grades, depth, and typical cross-section shown in the Plans or as established by the Engineer.

**4-02.2 Materials**

Materials shall meet the requirements of the following section:

Gravel Base

[9-03.10](#)

**4-02.3 Construction Requirements**

Gravel base shall be uniformly spread upon the prepared Subgrade to the depth, width, and cross-section shown in the Plans. Construction methods used shall meet the applicable requirements of [Sections 4-04.3](#).

**4-02.4 Measurement**

Gravel base will be measured in the same manner prescribed for the measurement of crushed surfacing materials as set forth in [Section 4-04.4](#) except as follows:

Where gravel base is specified, the Contractor may elect to substitute materials as described in [Section 3-01.4\(4\)](#). Crushed surfacing and gravel borrow, used in lieu of gravel base, will be measured and paid for as gravel base. In no case shall crushed surfacing, used in lieu of gravel base, be included in any Bid items for crushed surfacing.

**4-02.5 Payment**

Payment will be made in accordance with [Section 1-04.1](#), for the following Bid item when shown in the Proposal:

“Gravel Base”, per ton, or per cubic yard.